

## Grounding Cords

Our grounding cords can meet and surpass any rigid specification and possess an exceptionally long service life. All cords are insulated with Polyurethane.

- 100% retraction
- 1 mohm resistor
- 3 mm snap
- Banana plug/alligator clip termination or 7 mm snap termination
- meet or exceed IEC 61340-5-1, MIL HDBK 263B, MIL STD 1686B and ANSI/ESD-S1.1-2006

Grounding Cords			
Item No.	Colour	Length	Termination
1600929	dark blue	360 cm	3 mm B/A
1600926	dark blue	180 cm	3 mm B/A
1600931	black	180 cm	3 mm B/A

B/A = banana plug/alligator clip

Grounding Cords			
Item No.	Colour	Length	Termination
1600928	dark blue	360 cm	3 mm→7 mm
1600924	dark blue	180 cm	3 mm→7 mm



## Common Point Grounds

Common Point Grounds take care of the proper grounding of the operator and worksurface mat. by using an Adapt A Snap additional personnel can quickly plug into the ESD safe workstation and can be properly grounded.

- 450 cm straight grounding cord
- quick release snap with full 360° swivel
- dark blue
- 1 Mohm resistor
- meet or exceed IEC 61340-5-1, MIL HDBK 263B, MIL STD 1686B and ANSI/ESD-S1.1-2006

Common Point Grounds		
Item No.	Mat connection	Termination
1600886	7 mm female/ 7 mm male	B/A
1600885	7 mm female/10 mm male	B/A

B/A = banana plug/alligator clip

